



## Primary Cellular Alarm Communicator

The Uplink<sup>®</sup> CDMAEX is a primary cellular alarm communicator that features full event or summary event reporting. It offers dial-capture and smart siren/bell sampling to detect burglary or fire conditions, one output and trouble reporting for universal compatibility with almost every alarm system and central station.

The Uplink CDMAEX communicates to central stations by dialup to any industry standard receiver, or over the internet to an IP receiver — all with the exceptional service and features you've come to expect from Uplink, the leading supplier of wireless security solutions.

### Uplink Value:

Supports Uplink Remote for Interactive Control

Flat-rate billing for improved dealer profitability

Customizable product marketing services through a simple e-commerce website

Live technical and activation support 8:00 a.m. to 8:00 p.m. EST, Monday through Friday

### Device Features:

- ✓ Supports virtually all security systems and multiple formats
- ✓ Power from the panel or other 12V DC power source
- ✓ Remote on-demand testing for status and signal strength
- ✓ Momentary or maintained keyswitch zones. No adapter board required
- ✓ Perfect for residential and commercial alarm systems
- ✓ Installs in minutes with complete end-to-end signal verification
- ✓ Smart siren bell sampling to detect burglary or fire condition

Specifications subject to change without notice.

# CDMAEX Primary Cellular Alarm Communicator



## A Trusted Partner

Uplink delivers the unique combination of technology, quality, options, and superior value that have made us the industry's trusted source for security solutions since 1996.

With hundreds of thousands of installed devices throughout the United States, Mexico, and Canada, Uplink has the experience and expertise to provide reliable, award winning products with first class support.

Uplink technology is certified by the ISO/IEC27001 information security management standard and backed by a web-based dealer support management tool.

For more information, visit the Uplink website dealer portal at [www.uplink.com](http://www.uplink.com).

## Technical Specifications

INPUTS	
Alarm Dial Capture	Full event reporting of Contact ID, SIA, Modem IIe/IIIa <sup>2</sup> , or Pulse 4/2 (:10, :20, or :40 PPS) internet or dialup
One Input	Connect to Siren/Bell (distinguishes between Burg/steady and Fire/pulsed) or programmable to 12 volts
OUTPUTS AND REPORTING	
Central Station	Contact ID, SIA, Modem IIe/IIIa <sup>2</sup> , or Pulse 4/2 (:10, :20, or :40 PPS) internet or dialup
One Relay Outputs	Configurable - normally closed
Other Reporting Methods	Email, Text Message
Automated Testing	Monthly, weekly, or daily
Status LEDs	<ul style="list-style-type: none"><li>• Signal strength</li><li>• Power</li><li>• Panel hook status</li><li>• Trouble</li><li>• Heartbeat</li></ul>
POWER REQUIREMENTS	
12V DC (200 mA constant, 600 mA peak)	Uninterrupted Class 2 power supply 12V DC/600 mA minimum required
RADIO	
Cellular Frequencies	850/1900 MHz
Transmit Power	Maximum allowable: <ul style="list-style-type: none"><li>• 1.0W at 1900 MHz</li><li>• 2.0W at 850 MHz</li></ul>
DIMENSIONS	
Height/Width/Depth (inches)	4.75/3.3/1.3
Antenna	3.75 inches

Specifications subject to change without notice.